AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A laminate for sealing an electrolyte or protecting an electrode of a battery, comprising

a metal layer,

an inert protective layer formed over the surface of the metal layer in contact with said metal layer, wherein the inert protective layer is a reaction product of an oxidizing reaction of the metal layer surface or of a chemical reaction of the metal layer surface with an acid, and

a layer of an adhesive resin comprised of a polyolefin modified by carboxyl group or a derivative thereof, formed over the inert protective layer and fusedly bonded with heat thereto.

2-4. (Cancelled)

5. (Previously Presented) The laminate as claimed in claim 1, wherein the metal layer is comprised of one or more metals selected from the group consisting of aluminum, nickel, copper, iron and alloys thereof.

6-7. (Cancelled)

- 8. (Previously Presented) The laminate as claimed in claim 1, wherein the adhesive resin is a graft-modified polyolefin resin obtained by graft-copolymerizing a polyolefin resin with an ethylenically unsaturated carboxylic acid.
- 9. (Previously Presented) The laminate as claimed in claim 8, wherein the graftmodified polyolefin resin is a graft-modified polyethylene resin or a graft-modified polypropylene resin.

10-13. (Cancelled)

Docket No.: 0992-0127P

14. (Previously Presented) A seal film for sealing an electrolyte of a battery or a protective film for protecting an electrode of a battery, which film is made from the laminate as

claimed in claim 1.

15. (Cancelled)

16. (Previously Presented) A seal film for sealing an electrolyte of a secondary battery

or a protective film for protecting an electrode of a secondary battery, which film is made from

the laminate as claimed in claim 1.

17-24. (Cancelled)

25. (Previously presented) The laminate as claimed in claim 1, wherein said inert

protective film is formed by an acid treatment of said metal layer.

26. (Previously Presented) The laminate as claimed in claim 25, wherein said acid is

selected from the group consisting of chromic acid, phosphoric acid, and mixtures thereof.

27. (Previously Presented) The laminate as claimed in claim 1, wherein said oxidative

treatment comprises anodic oxidation.

28-29. (Cancelled)

30. (New) The laminate as claimed in claim 1, wherein the adhesive resin has an adhesive

strength of 5.8 N/15 mm up to an adhesive strength rendering a film unpeelable when said film is

formed of the adhesive resin in direct contact with the inert protective or passive layer formed by

acid treatment of an aluminum layer.

3

MSW/GMD/mua

Application No. 10/069,001 Amendment dated September 5, 2006 filed with RCE After Final Office Action of June 5, 2006

31. (New) The laminate as claimed in claim 1, wherein the adhesive resin layer is in contact with the inert protective or passive layer, or the adhesive resin layer is in contact with a primer coating layer and the primer coating layer is in contact with the inert protective or passive layer.

Docket No.: 0992-0127P